

DME

Digital dosing pumps



1. General data	3
Performance range	3
Digital Dosing	4
2. Identification	5
Type key	5
3. Functions	6
Overview of functions	6
Functional description	7
Control panel	8
Menu	10
Operating modes	11
Control panel lock	13
Units	13
Wiring diagram DME-AR	14
4. Construction	16
5. Dimensions	17
6. Technical data	18
7. Pump selection	19
Standard range	19
Non-standard range	20
8. Pumped liquids	21
9. Grundfos Product Center	22

1. General data

Performance range




Fig. 1 Performance range DME

TM06 9628 2617

Digital Dosing

Digital Dosing represents state-of-the-art technology. This patented Grundfos solution sets new standards, including new principles and methods.



TM06 9627 2617

Fig. 2 DME pump

Precise and easy setting

The operator can easily install and set the pump to dose exactly the quantity of dosing medium required in the application. In the display, the setting of the pump is read out directly in ml/h or l/h, pulse or batch, and the operation mode is easily identified by means of icons.

Unique technology

A unique drive and microprocessor control ensure that the medium is dosed precisely and with low pulsation even if the pump is operating with high-viscosity or degassing media. Instead of the conventional stroke-length adjustment, the capacity of the DME is regulated by automatic adjustment of the motor speed during the discharge stroke and by fixed suction stroke speed, ensuring optimal and uniform mixing.

Fewer variants to cover all needs

DME pumps feature a powerful variable-speed motor, a turn-down ratio of 1:800 and a complete control interface including:

- Full pulse control
- Pulse-based batch control
- Internal timer-based batch control
- Analog 0/4-20 mA control
- Level control
- Fieldbus communication module.

This ensures that the DME pumps cover the range from 375 to 940 litres per hour up to 10 bar. The switch mode power supply ensures that the same pump is working precisely, irrespective of the mains supply (100-240 V, 50/60 Hz).

The DME dosing pumps feature diaphragm dosing head with integrated vent valve, ball valves at the inlet and outlet. The pumps are fitted with power cable and plug.

2. Identification

Type key

Type	DME 375-10 AR-PP/E/C-F-31A1F
Maximum capacity [l/h]	DME 375-10 AR-PP/E/C-F-31A1F 375 940
Maximum pressure [bar]	DME 375-10 AR-PP/E/C-F-31A1F 4 10
Control variant	DME 375-10 AR-PP/E/C-F-31A1F AR Standard AP Standard + Profibus B Basic
Dosing head material	DME 375-10 AR-PP/E/C-F-31A1F PP Polypropylene PV PVDF SS Stainless steel 1.4401
Gasket material	DME 375-10 AR-PP/E/C-F-31A1F E EPDM T PTFE V FKM
Valve ball material	DME 375-10 AR-PP/E/C-F-31A1F C Ceramic G Glass SS Stainless steel 1.4401 T PTFE
Control panel	DME 375-10 AR-PP/E/C-F-31A1F F Front-fitted S Side-fitted
Voltage	DME 375-10 AR-PP/E/C-F-31A1F 3 1 x 100-240 V, 50/60 Hz
Valve type	DME 375-10 AR-PP/E/C-F-31A1F 1 Standard valve 2 Spring-loaded valve
Connection, inlet/outlet	DME 375-10 AR-PP/E/C-F-31A2F A2 Threaded, Rp 1 1/4" A4 Threaded, NPT 1 1/4"
Mains plug	DME 375-10 AR-PP/E/C-F-31A1F F EU (Schuko) G UK I Australia (AU) B USA J Japan (JP) E Switzerland (CH) L Argentina

3. Functions

Overview of functions

Control variant	DME-B	DME-AR	DME-AP
Capacity control, see page 11			
Internal stroke-frequency control	•	•	•
Internal stroke-speed control	•	•	•
Control panel, see page 8			
Capacity setting in litres, millilitres or US gallons	•	•	•
Display with background light and soft-touch buttons	•	•	•
Easy set-up menu with language options	•	•	•
On/Off button	•	•	•
Maximum capacity button (priming)	•	•	•
Green indicator light for operating indication	•	•	•
Red indicator light for fault indication	•	•	•
Control panel lock	•	•	•
Side-fitted as an option	•	•	•
Operating modes, see page 11			
Manual control	•	•	•
Pulse control		•	•
Analog 0/4-20 mA control		•	•
Timer-based batch control		•	•
Pulse-based batch control		•	•
Functions, see page 12/13			
Dual-level control		•	•
Calibration of the pump for the actual installation	•	•	•
Anti-cavitation (reduced suction speed)	•	•	•
Capacity limitation	•	•	•
Counters for strokes, operating hours and power on/off	•	•	•
Fieldbus communication			•
Overload protection	•	•	•
Error message in display	•	•	•
Diaphragm leakage sensor ★		•	•
Dosing signal output		•	•
Power supply, see page 13			
Switch-mode power supply		•	•
Inputs/outputs, see page 15/15			
Input for pulse control		•	•
Input for analog 0/4-20 mA control		•	•
Input for dual-level control		•	•
Input for external start/stop		•	•
Alarm relay output (variant AR)		•	•
Dosing output		•	•
Input for external on/off switch		•	•

★ When dosing crystallising media, a diaphragm leakage sensor must be installed. DME-B is not suitable for crystallising media.

Functional description

The electronically controlled variable-speed motor of the DME pump provides optimum control of the stroke speed. As shown in the figure below, the duration of each suction stroke is constant while the duration of each discharge stroke varies according to the capacity set, resulting in optimum discharge flow in any operating situation.

The advantages:

- The pump always operates at full stroke length, irrespective of the capacity set; this ensures optimum accuracy, priming and suction.
- A capacity range of 1:800 for each pump size.
- Smooth and constant dosing ensuring an optimum mixing ratio at the injection point.
- Significant reduction of pressure surges preventing mechanical stress on diaphragm, hoses, pipes, connections and other dosing parts exposed to leakage and wear.
- The installation is less affected by long inlet and outlet lines.
- Easier dosing of highly viscous and gas-containing liquids.

Capacity setting




Fig. 3 Relation between stroke-frequency adjustment and capacity

TM01 8944 0900

Control panel




Fig. 4 Control panel

TM04 8481 0612

Pos.	Description
1	Maximum capacity button (priming)
2	Navigation/settings
3	Menu/accept
4	LCD display
5	Navigation/settings
6	Green indicator light
7	Red indicator light
8	On/Off button



Fig. 5 Front-fitted control panel


TM04 8702 5112






Fig. 6 Side-fitted control panel

TM04 8703 5112
















Maximum capacity button

If the maximum capacity is required over a short period of time, for example during start-up, press the  button on the pump control panel. When the button is released, the pump automatically returns to the previous operating mode.

To set the pump to run for a specific number of seconds at maximum capacity, press the  and  buttons simultaneously. The remaining number of seconds appear in the display. The maximum value is 300 seconds. To stop the pump before the set time has passed, press the  button.

This feature is useful when flushing the pump.


Indicator lights and alarm relay output

Condition	Green LED	Red LED	Display	Alarm output
Pump running	On	Off	Normal indication	
Set to stop	Flashing	Off	Normal indication	
Pump fault	Off	On	EEPROM	
Supply failure	Off	Off	Off	
Pump running, low chemical level ^{★1}	On	On	LOW	
Empty tank ^{★1}	Off	On	EMPTY	
Analog signal < 2 mA	Off	On	NO mA	
The pump is running, but the dosed quantity is too small according to the signal from the dosing monitor ^{★2}	On	On	NO FLOW	
Overheating	Off	On	MAX TEMP	
Internal communication fault	Off	On	INT. COM.	
Internal Hall fault ^{★3}	Off	On	HALL	
Diaphragm (leakage) ^{★4}	Off	On	LEAKAGE	
Max. pressure exceeded ^{★4}	Off ^{★5}	On	OVERLOAD	
More pulses than capacity	On	On	MAX. FLOW	
No motor rotation detected ^{★3}	Off	On	ORIGO	

★1 Requires connection to level sensors. See [Level control](#), page 13.


★2 Requires activation of the dosing monitoring function and connection to a dosing monitor.

★3 Please contact a Grundfos service centre.

★4 Alarms can be reset  when the faults have been corrected.

★5 The pump will make 10 attempts to restart before going into permanent OFF mode.

Menu

The DME dosing pumps feature a user-friendly menu. To activate the menu, press the button . During initial start-up, all menu texts appear in the English language. You can set the menu to display other languages, see page 13.




Fig. 7 Menu overview

TMD4 8484 0612

Operating modes

Manual control

The pump ensures constant dosing according to the quantity set in l/h or ml/h by means of the ◀ and ▶ buttons. The pump automatically changes between the measuring units.

Setting range

Pump type	Setting range	
	From [ml/h]	To [l/h]
DME 375	500	375
DME 940	1200	940

When the anti-cavitation functions is enabled, the maximum flow is reduced (see page 12).

Pulse control

Applies to DME-AR and DME-AP

The pump doses according to an external pulse signal, for example from a water meter.

There is no direct relation between pulses and dosing strokes. The pump automatically calculates its optimal speed to ensure that the required quantity is dosed for each pulse. The quantity to be dosed is set in ml/pulse. The pump adjusts its speed and/or stroke frequency according to two factors:

- The frequency of external pulses
- The set quantity per pulse.

Setting range

Pump type	Setting range [ml/pulse]
DME 375-10	0.00392 - 750
DME 940-4	0.00980 - 1880

Analog 0/4-20 mA control

Applies to DME-AR and DME-AP

The pump ensures dosing according to an external analog signal. The dosed capacity is proportional to the input value in mA.

Setting	Input signal	Dosed quantity as a percentage of the max. capacity*
4-20 (default):	4 mA	0 %
	20 mA	100 %
20-4:	4 mA	100 %
	20 mA	0 %
0-20:	0 mA	0 %
	20 mA	100 %
20-0:	0 mA	100 %
	20 mA	0 %

* If a maximum capacity limitation has been set, the dosed quantity is a percentage of the set capacity limitation (see page 12).




Fig. 8 4-20 mA control

Timer-based batch control

Applies to DME-AR and DME-AP

The set quantity is dosed in batches at maximum capacity or the set capacity limitation.

The time until the first dosing (NX) and the following sequences (IN) can be set in minutes, hours and days. The maximum time limit is 9 days, 23 hours and 59 minutes (9:23:59). The lowest acceptable value is one minute. IN must be higher than the time required to perform one batch. If IN is lower than the time required, the next batch will be ignored.

In case of supply failure, the set dosing quantity, the IN time and the remaining NX time are stored. When the supply is reconnected, the pump starts up with the NX time at the time of the supply failure. Thus, the timer cycle continues, but it will be delayed according to the time of the supply failure.




Fig. 9 Timer-based batch control

Setting range

Pump type	Setting range	
	From [ml/batch]	To [l/batch]
DME 375	39.1	750
DME 940	97.9	1880

Pulse-based batch control

Applies to DME-AR and DME-AP

The set quantity is dosed in batches at maximum capacity or the set capacity limitation. The quantity is dosed every time the pump receives an external pulse. If the pump receives new pulses before the batch is completed, these pulses will be ignored.




Fig. 10 Pulse-based batch control

TM04 8831 1513

Setting range

Pump type	Setting range	
	From [ml/batch]	To [l/batch]
DME 375	39.1	750
DME 940	97.9	1880

Anti-cavitation

When the anti-cavitation function is selected, the pump extends and smooths its suction stroke. This results in a softer suction stroke.

The anti-cavitation function is used in these situations:

- When pumping high-viscosity liquids
- When pumping degassing liquids
- When the inlet line is long
- When the suction lift is high.

Depending on the circumstances, the motor speed during the suction stroke can be reduced to approximately 75 %, 50 % or 25 % of the normal motor speed. When using the anti-cavitation function, the maximum pump capacity is reduced.

Maximum capacity limitation

Maximum capacity limitation makes it possible to reduce the maximum capacity (MAX. CAP). It influences the functions in which the pump normally operates at maximum capacity. Under normal operating conditions, the pump cannot operate at a capacity higher than the one stated in the display. When pushing the maximum capacity button, the pump operates at 100 %.

With the maximum capacity limitation function, a large pump can be set to operate as a much smaller pump. Together with the 1:800 capacity range, this function allows the following:

1. To utilize the smooth and even dosing characteristics of the pump at low capacities to achieve
 - improved chemical mixing
 - improved dosing through long outlet lines
 - improved dosing of high-viscosity liquids.

2. To improve the dosing of gas-containing liquids: In a large pump, the displaced volume (1) is much larger than the non-displaced volume (2).




Fig. 11 Anti-cavitation

TM04 8832 1513

3. To cover several needs with just one pump size.
4. To adapt the pump to a 4-20 mA signal control with 4 mA corresponding to 0 % and 20 mA to the set maximum capacity.

This allows you to use a DME for dosing a very small quantity of liquid without having to change the input signal.

Example:

A DME 375 receives a 12 mA input signal from a control instrument. According to the analog curve (see page 11), this results in a 50 % output and a capacity of 188 l/h.

A new situation occurs where it is only necessary to dose 47 l/h: The maximum capacity limitation is set to 94 l/h. The pump is still receiving a 12 mA signal resulting in a 50 % output and a capacity of 47 l/h.




Fig. 12 Maximum capacity limitation

TM06 9631 2617

The maximum capacity limitation also reduces the pump speed in timer-based batch control, pulse-based batch control and during calibration where the pump usually operates at maximum capacity.

Calibration

After start-up, the dosing pumps can be calibrated for the actual installation to ensure that the displayed value (millilitres or litres) is correct. A calibration program in the set-up menu facilitates calibration.

Counters

The pump can display non-resettable counters for:

- "Quantity":
Accumulated dosed quantity in litres or US gallons.
- "Strokes":
Accumulated number of dosing strokes.
- "Hours":
Accumulated number of operating hours (power on).
- "Power ON":
Accumulated number of times the mains supply has been switched on.

Languages

The display text can be displayed in one of the following languages chosen in the set-up menu:

- English, German, French, Italian, Spanish, Portuguese, Dutch, Swedish, Finnish, Danish, Czech, Slovak, Polish, Russian.

Integrated vent valve

The DME dosing pumps are provided with an integrated vent valve (1). The vent valve makes priming during start-up very easy.

The vent valve must be connected to the tank by means of a 15/20 mm PVC hose.




Fig. 13 Integrated vent valve

Switch-mode power supply

The DME pump incorporates a switch-mode power supply. This makes the pump independent of variations in supply voltage and frequency.

Operating range: 1 x 100-240 V, 50/60 Hz.

Level control

Applies to DME-AR and DME-AP

The pump can be connected to a level control unit for monitoring of the chemical level in the tank. The pump can react to two level sensor signals.

Level sensors	Pump reaction
Upper sensor activated	<ul style="list-style-type: none"> • Red indicator light is on. • Pump is running. • Alarm relay is activated.★
Lower sensor activated	<ul style="list-style-type: none"> • Red indicator light is on. • Pump stops. • Alarm relay is activated.★

★ Applies to control variant AR.

Bus communication

The DME-AP is available with a built-in module for bus communication with PROFIBUS DP systems. This module enables remote monitoring and setting via the fieldbus system.

All DME features are available via bus communication. The PROFIBUS GSD-files can be found on the product CD included in the standard delivery.

Diaphragm leakage sensor

The pump can be fitted with a diaphragm leakage sensor. The sensor is connected to the drain hole of the dosing head. In case of leakage of the diaphragm, the signal from the sensor generates an alarm in the pump, and the alarm relay is activated. When dosing crystallising media, a diaphragm leakage sensor must be installed.

Control panel lock

It is possible to lock the buttons on the control panel to prevent maloperation of the pump. The locking function can be set to ON or OFF. The default setting is OFF.

A PIN code is required to change from OFF to ON. When ON is selected for the first time, "_____" appears in the display. If a code has already been entered, the code will appear when an attempt to change to ON is made. This code can either be re-entered or changed.

Units

It is possible to select metric units (litre/millilitre) and US units (gallons/millilitre).

Metric measuring units

- In manual and analog modes, set the quantity to be dosed in litres per hour (l/h) or millilitres per hour (ml/h).
- In pulse mode, set the quantity to be dosed in ml/pulse. The actual capacity is indicated in litres per hour (l/h) or millilitres per hour (ml/h).
- For calibration, set the quantity to be dosed in ml per 100 strokes.
- In timer and batch modes, set the quantity to be dosed in litres (l) or millilitres (ml).

Under the QUANTITY menu item in the COUNTERS menu, the dosed quantity is indicated in litres.

US measuring units

- In manual and analog modes, set the quantity to be dosed in gallons per hour (gph).
- In pulse mode, set the quantity to be dosed in ml/pulse. The actual capacity is shown in gallons per hour (gph).
- For calibration, set the quantity to be dosed in ml per 100 strokes.
- In timer and batch modes, set the quantity to be dosed in gallons.

Under the QUANTITY menu item in the COUNTERS menu, the dosed quantity is indicated in gallons (gal).




Fig. 14 Possible units settings

TM04 8762 1213

Wiring diagram DME-AR




Fig. 15 Wiring diagram DME-AR

TM02 7069 2503

Table 1: Input for analog, pulse and leakage sensor

Function	Pin holes					Plug type
	1/brown	2/white	3/blue, 5 V	4/black	5/grey	
Pulse	X		X			contact
Pulse	5 V			GND		5 VDC
Analog				(-) mA input	(+) mA input	mA signal
Batch	X		X			contact
Batch input	5 V			GND		5 VDC
		2/black	3/brown	4/blue		
Leakage sensor		X	X			contact
Leakage sensor		5 V		GND		5 VDC

Table 2: Output for alarm relay

Function	Pin holes		
	1/brown	2/white	3/blue
Alarm relay output NO	X	X	
Alarm relay output NC	X		X

Table 3: Input for external stop, output for dosing

Function	Pin holes					Plug type
	1/brown	2/white	3/blue, 5 V	4/black	5/grey	
External stop input	X		X			contact
External stop input	5 VDC			GND		5 VDC
Dosing output (pump running)		open collector*	X	GND		NPN



* With internal 5 VDC power supply: max. 100 mA, with external power supply: max. 24 VDC, 100 mA.

"Open collector" with internal 5 VDC power supply

The 5 VDC relay is connected to the "open collector" and the 5 VDC pin. It can switch an electrical appliance with independent power supply.

"Open collector" with external 24 VDC power supply


The electrical appliance with 24 VDC power supply is connected to the open collector and GND.

**Fig. 16** How to use the "open collector" output signal**Table 4: Input for level sensor**

Function	Pin holes					Plug type
	1/brown	2/white	3/blue, 5 V	4/black	5/grey	
Low level	X*		X*			contact
Low level	5 V			GND		5 VDC
Empty tank		X*	X*			contact
Empty tank		5 V		GND		5 VDC

* The function for the potential-free contact set can be chosen from the display (NO = Normally Open and NC = Normally Closed).

4. Construction



TM06 9633 2617

Fig. 17 Sectional drawing

Material specification

Pos.	Description	Material options
1	Back plate	PPE/PS 20 % glass fibre
2	Spring	DIN 17223 TYPE C
3	Housing	PPE/PS 20 % glass fibre
4	Hall sensor	-
5	Operation PCB	-
6	Power cable	Rubber
7	Gear	-
8	Brushless DC motor	-
10	Connection with internal thread 1 1/4" NPT / Rp 1 1/4	PP/PVDF
11	Union nut	PP/PVDF
12	Connection, complete	-
14	O-ring	EPDM/FKM/PTFE
15	Vent valve, ball	Ceramic
16	Spring	Alloy C-4, 2.4610 (NiMo16CrTi)
17	Spring	Alloy C-4, 2.4610 (NiMo16CrTi)
18	Vent valve, body	PP/PVDF
19	Vent valve, tap	PP/PVDF
20	O-ring	EPDM/FKM/PTFE
21	End cover	Steel
22	Vent valve, complete	-
23	O-ring	EPDM/FKM/PTFE
24	Valve seat	PP/PVDF/SS 1.4401/PTFE
25	Valve ball	Ceramic/Glass/SS 1.4401/ PTFE

Pos.	Description	Material options
26	Valve casing	PP/PVDF/SS 1.4401
27*	Spring	Alloy C-4, 2.4610 (NiMo16CrTi)
28	O-ring	EPDM/FKM/PTFE
29	Valve, complete	-
30**	Dosing head cover	Steel
31	Dosing head	PP/PVDF/SS 1.4401
32	Safety membrane	-
33	Power PCB	-
34	Crank shaft	Steel
35	I/O PCB	-
36	Connecting rod	Steel
37	Steel plate	Steel
38	Steel frame	Steel
39	Diaphragm	Textile-reinforced EPDM, PTFE-coated

* The pump is available with spring-loaded valves.
Spring material: Alloy C-4, 2.4610 (NiMo16CrTi)

** The steel plate is not included in the stainless-steel dosing head version.

5. Dimensions




Fig. 18 Dimensions of DME 375 and DME 940

Pump type	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]
DME 375	238	218	410	364	230	543	95	95	246
DME 940	238	218	430	364	230	543	75	95	246

DME 375 and DME 940 are equipped with 1 1/4" thread connections.

6. Technical data

DME		DME 375	DME 940	
Mechanical data	Maximum capacity	[l/h]	376	940
	Maximum capacity with anti-cavitation function, 75 %	[l/h]	282	705
	Maximum capacity with anti-cavitation function, 50 % (approx.)	[l/h]	210	525
	Maximum capacity with anti-cavitation function, 25 % (approx.)	[l/h]	101	252
	Maximum pressure	[bar]	10	4
	Maximum stroke frequency	[stroke/min]	160	
	Maximum suction lift during operation	[m]	6	
	Maximum suction lift when priming with wet valves	[m]	1.5	
	Maximum viscosity with spring-loaded valves*	[mPas] (= cP)	3000 mPas at 50 % capacity	
	Maximum viscosity without spring-loaded valves*	[mPas] (= cP)	200	
	Maximum liquid temperature	[°C]	50	
	Minimum liquid temperature	[°C]	0	
	Maximum ambient temperature	[°C]	45	
	Minimum ambient temperature	[°C]	0	
Accuracy of repeatability	[%]	± 1		
Weight and size	Weight	[kg]	21	22.5
	Diaphragm diameter	[mm]	124	173
Electrical data	Supply voltage	[VAC]	1 x 100-240 V, 50/60 Hz	
	Maximum current consumption at 100 V	[A]	2.40	
	Maximum current consumption at 230 V	[A]	1.0	
	Maximum power consumption P ₁	[W]	240	
	Enclosure class		IP65	
	Insulation class		B	
	Power supply cable	[m]	1.5 H05RN-F with plug	
Signal input	Voltage in level sensor input	[VDC]	5	
	Voltage in pulse input	[VDC]	5	
	Minimum pulse-repetition period	[ms]	3.3	
	Impedance in analog 0/4-20 mA input	[Ω]	250	
	Maximum loop resistance in pulse signal circuit	[Ω]	250	
	Maximum loop resistance in level signal circuit	[Ω]	250	
Signal output	Maximum load of alarm relay output, at ohmic load	[A]	2	
	Maximum voltage, alarm relay output	[V]	42	
Sound pressure level	Maximum sound pressure level	[dB(A)]	70	
Approvals			CE, cCSAus, EAC	

* Maximum suction lift: 1 metre.

7. Pump selection

Standard range

Power supply: 1 x 100-240 V, 50/60 Hz switch-mode

Mains plug: EU (Schuko)

Valves: Single-ball valve on inlet side; single-ball valve on outlet side

Max. capacity [l/h]	Max. pressure [bar]	Control variant	Materials			Connection ^{★1}	Control panel position	Type designation	Product No.			
			Dosing head	Gaskets	Valve balls							
375	10	AR	PP	EPDM	Glass	Rp 1 1/4	Front	DME 375-10 AR-PP/E/G-F-31A2A2F	96524941			
							Side	DME 375-10 AR-PP/E/G-S-31A2A2F	96524942			
			PP	FKM	Glass	Rp 1 1/4	Front	DME 375-10 AR-PP/V/G-F-31A2A2F	96524943			
							Side	DME 375-10 AR-PP/V/G-S-31A2A2F	96524944			
			PVDF	FKM	Glass	Rp 1 1/4	Front	DME 375-10 AR-PV/V/G-F-31A2A2F	96524945			
							Side	DME 375-10 AR-PV/V/G-S-31A2A2F	96524946			
			SS	PTFE	SS 1.4401	Rp 1 1/4	Front	DME 375-10 AR-SS/T/SS-F-31A2A2F	96987377			
							Side	DME 375-10 AR-SS/T/SS-S-31A2A2F	97503530			
			375	10	B ^{★2}	PP	EPDM	Glass	Rp 1 1/4	Front	DME 375-10 B-PP/E/G-F-31A2A2F	96524949
										Side	DME 375-10 B-PP/E/G-S-31A2A2F	96524950
PP	FKM	Glass				Rp 1 1/4	Front	DME 375-10 B-PP/V/G-F-31A2A2F	96524951			
							Side	DME 375-10 B-PP/V/G-S-31A2A2F	96524952			
PVDF	FKM	Glass				Rp 1 1/4	Front	DME 375-10 B-PV/V/G-F-31A2A2F	96524953			
							Side	DME 375-10 B-PV/V/G-S-31A2A2F	96524954			
SS	PTFE	SS 1.4401				Rp 1 1/4	Front	DME 375-10 B-SS/T/SS-F-31A2A2F	97503531			
							Side	DME 375-10 B-SS/T/SS-S-31A2A2F	97503532			
940	4	AR				PP	EPDM	Glass	Rp 1 1/4	Front	DME 940-4 AR-PP/E/G-F-31A2A2F	96524958
										Side	DME 940-4 AR-PP/E/G-S-31A2A2F	96524959
			PP	FKM	Glass	Rp 1 1/4	Front	DME 940-4 AR-PP/V/G-F-31A2A2F	96524960			
							Side	DME 940-4 AR-PP/V/G-S-31A2A2F	96524961			
			PVDF	FKM	Glass	Rp 1 1/4	Front	DME 940-4 AR-PV/V/G-F-31A2A2F	96524962			
							Side	DME 940-4 AR-PV/V/G-S-31A2A2F	96524963			
			SS	PTFE	SS 1.4401	Rp 1 1/4	Front	DME 940-4 AR-SS/T/SS-F-31A2A2F	97503533			
							Side	DME 940-4 AR-SS/T/SS-S-31A2A2F	97503534			
			940	4	B ^{★2}	PP	EPDM	Glass	Rp 1 1/4	Front	DME 940-4 B-PP/E/G-F-31A2A2F	96524966
										Side	DME 940-4 B-PP/E/G-S-31A2A2F	96524967
PP	FKM	Glass				Rp 1 1/4	Front	DME 940-4 B-PP/V/G-F-31A2A2F	96524968			
							Side	DME 940-4 B-PP/V/G-S-31A2A2F	96524969			
PVDF	FKM	Glass				Rp 1 1/4	Front	DME 940-4 B-PV/V/G-F-31A2A2F	96524980			
							Side	DME 940-4 B-PV/V/G-S-31A2A2F	96524981			
SS	PTFE	SS 1.4401				Rp 1 1/4	Front	DME 940-4 B-SS/T/SS-F-31A2A2F	97503537			
							Side	DME 940-4 B-SS/T/SS-S-31A2A2F	97503538			

^{★1} Rp 1 1/4 connections have internal thread for pipe connection.

^{★2} DME-B is not suitable for crystallising media.

Non-standard range

Maximum capacity - pressure	[l/h]-[bar]	DME 375-10: 375 l/h - 10 bar; DME 940-4: 940 l/h - 4 bar	
Control variant	B:	Basic	
	AR:	Standard	
	AP:	Standard + Profibus	
Material	Dosing head	PP:	Polypropylene
		PV:	PVDF
		SS:	Stainless steel 1.4401
	Gaskets	E:	EPDM
		V:	FKM
		T:	PTFE
Valve balls	C:	Ceramic	
	SS:	Stainless steel 1.4401	
	G:	Glass	
Control panel position	T:	PTFE	
	F:	Front	
Voltage	S:	Side	
	3:	1 x 100-240 V, 50/60 Hz	
Valve type	1:	Standard	
	2:	Spring-loaded	
Connection inlet/outlet	A2:	Threaded, Rp 1 1/4	
	A4:	Threaded, 1 1/4" NPT	
Mains plug	F:	EU (Schuko)	
	B:	USA	
	G:	UK	
	I:	Australia (AU)	
	E:	Switzerland (CH)	
	J:	Japan (JP)	
	L:	Argentina	

DME	Control variant	Materials			Control panel position	Voltage	Valve type	Connection inlet/outlet	Mains plug
		Head	Gaskets	Balls					
375-10 940-4	B AR AP	PP	E V	C G SS	-F -S-	3	1 2	A2A2 A4A4	F B I E J L
		PV	E V	C G SS					
			T	C G SS T					
		SS	E V T	SS					

8. Pumped liquids

The resistance table below is intended as a general guide for material resistance (at room temperature), and does not replace testing of the chemicals and pump materials under specific working conditions.

The data shown are based on information from various sources available, but many factors (purity, temperature, abrasive particles, etc.) may affect the chemical resistance of a given material.

Note: Some of the liquids in this table may be toxic, corrosive or hazardous. Please be careful when handling these liquids.

Pumped liquid (20 °C)			Materials						
			Dosing head			Gasket			Ball
Description	Chemical formula	Concentration [%]	PP	PVDF	SS 1.4401	FKM	EPDM	PTFE	Ceramic
			Acetic acid	CH ₃ COOH	25	•	•	•	-
		60	•	•	•	-	•	•	•
		85	•	•	○	-	-	•	•
Aluminium chloride	AlCl ₃	40	•	•	-	•	•	•	•
Aluminium sulphate	Al ₂ (SO ₄) ₃	60	•	•	•	•	•	•	•
Ammonia, aqueous	NH ₄ OH	28	•	•	•	-	•	•	•
Calcium hydroxide* ⁵	Ca(OH) ₂		•	•	•	•	•	•	•
Calcium hypochlorite	Ca(OCl) ₂	20	○	•	-	•	•	•	•
		10	•	•	•	•	•	•	•
Chromic acid* ³	H ₂ CrO ₄	30	-	•	-	•	○	•	•
		40	-	•	-	•	-	•	•
		50	-	•	-	•	-	•	•
Copper sulphate	CuSO ₄	30	•	•	•	•	•	•	•
Ferric chloride* ¹	FeCl ₃	60	•	•	-	•	•	•	•
Ferric sulphate* ¹	Fe ₂ (SO ₄) ₃	60	•	•	•	•	•	•	•
Ferrous chloride	FeCl ₂	40	•	•	-	•	•	•	•
Ferrous sulphate	FeSO ₄	50	•	•	•	•	•	•	•
Hydrochloric acid	HCl	< 25	•	•	-	○	•	•	•
		25-37	•	•	-	-	•	•	•
Hydrogen peroxide	H ₂ O ₂	30	•	•	•	•	•	•	•
		10	•	•	•	•	•	•	•
Nitric acid	HNO ₃	30	•	•	•	•	•	•	•
		40	○	•	•	•	•	•	•
		70	-	•	•	•	-	•	•
Peracetic acid	CH ₃ COOOH	5	•	•	-	-	•	•	•
Potassium hydroxide	KOH	50	•	-	•	-	•	•	•
Potassium permanganate	KMnO ₄	10	•	•	•	-	•	•	•
Sodium chlorate	NaClO ₃	30	•	•	•	○	•	•	•
Sodium chloride	NaCl	30	•	•	-	•	•	•	•
Sodium chlorite	NaClO ₂	20	•	○	-	•	•	•	•
		20	•	○	•	•	•	•	•
Sodium hydroxide	NaOH	30	•	-	•	•	•	•	•
		50	•	-	•	•	•	•	•
Sodium hypochlorite	NaOCl	20	○	•	-	•	•	•	•
Sodium sulphide	Na ₂ S	30	•	•	•	•	•	•	•
Sodium sulphite* ⁴	Na ₂ SO ₃	20	•	•	•	•	•	•	•
Sulphurous acid	H ₂ SO ₃	6	•	•	•	•	•	•	•
Sulphuric acid* ²	H ₂ SO ₄	< 80	•	•	-	•	○	•	•
		80-98	○	•	-	•	-	•	•

• Resistant

○ Limited resistance

- Not resistant

★1 Risk of crystallisation. DME-B is not suitable for crystallising media.

★2 Reacts violently with water and generates much heat. (Pump should be absolutely dry before dosing sulphuric acid.)

★3 Must be fluoride-free when glass balls are used.

★4 In neutral solutions.

★5 Saturated solution 0.1 %.

Further information:

<http://product-selection.grundfos.com/liquids.html>

9. Grundfos Product Center

Online search and sizing tool to help you make the right choice.

<http://product-selection.grundfos.com>



"SIZING" enables you to size a pump based on entered data and selection choices.

"REPLACEMENT" enables you to find a replacement product. Search results will include information on the following:

- the lowest purchase price
- the lowest energy consumption
- the lowest total life cycle cost.

The screenshot shows the Grundfos Product Center website. At the top, there is a navigation bar with the Grundfos logo and 'PRODUCT CENTER'. Below this is a search bar with a 'SEARCH' button. The main content area features four large buttons: 'SIZING' (with a subtext 'Enter pump sizing'), 'CATALOGUE' (with a subtext 'Products and services'), 'REPLACEMENT' (with a subtext 'Replace an old pump with a new'), and 'LIQUIDS' (with a subtext 'Find pump by liquid'). Below these buttons is a 'QUICK SIZING' section with input fields for 'Flow (Q)*' and 'Head (H)*', and radio buttons for 'Select what to size by: Size by application', 'Size by pump design', and 'Size by pump family'. A 'START SIZING' button is also present. At the bottom of the screenshot, there are links for 'ADVANCED SIZING' with options for 'Advanced sizing by application' and 'Guided selection'.

www.grundfos.com Login

GRUNDFOS | PRODUCT CENTER Product range: United Kingdom | 50 Hz | Language: English
Change settings

HOME FIND PRODUCT COMPARE YOUR PROJECTS SAVED ITEMS HELP 1.4.23

FIND PRODUCTS AND SOLUTIONS

Input a product number or a whole or partial product name

SIZING
Enter pump sizing

CATALOGUE
Products and services

REPLACEMENT
Replace an old pump with a new

LIQUIDS
Find pump by liquid

QUICK SIZING

Enter duty point:

Flow (Q)* m³/h

Head (H)* m

Select what to size by:

Size by application

Size by pump design

Size by pump family

START SIZING

ADVANCED SIZING: Advanced sizing by application Guided selection

"CATALOGUE" gives you access to the Grundfos product catalogue.

"LIQUIDS" enables you to find pumps designed for aggressive, flammable or other special liquids.

All the information you need in one place

Performance curves, technical specifications, pictures, dimensional drawings, motor curves, wiring diagrams, spare parts, service kits, 3D drawings, documents, system parts. The Product Center displays any recent and saved items - including complete projects - right on the main page.

Downloads

On the product pages, you can download installation and operating instructions, data booklets, service instructions, etc. in PDF format.

be think innovate

98455369 0218

ECM: 1211746

GRUNDFOS A/S
DK-8850 Bjerringbro . Denmark
Telephone: +45 87 50 14 00
www.grundfos.com

GRUNDFOS 

© Copyright Grundfos Holding A/S

The name Grundfos, the Grundfos logo, and be think innovate are registered trademarks owned by Grundfos Holding A/S or Grundfos A/S, Denmark. All rights reserved worldwide.